

Colorado Pro 600

Interior Latex Paint

0650 Series Flat

Description:

Colorado Pro 600 Interior Flat 0650 Series is a professional maintenance quality interior latex paint that meets the requirements of painters, contractors and building managers. Ideal for interior walls, trim and ceilings, this easy-to-apply product provides good hide, durability and touchup.

Features and Benefits:

Easy application and clean-up
Low VOC (< 50 g/L)
Good touchup
Provides a smooth, flat finish
Good hiding power
Reduced spatter

Application and Substrate Information:

Mix or stir thoroughly before using. All label and MSDS information should be read and understood prior to use. Paint should be applied using a nylon or polyester brush, roller, or via airless spray equipment (2,000 psi, 0.015" to 0.021" tip). A second coat may be applied 4 hours after applying the first coat.

All substrates should be clean, dry, and free of dirt, wax, loose or peeling paint, and otherwise be in sound condition. May be applied to properly prepared gypsum board, drywall, concrete/masonry block, plaster, wood, and metal. See Surface Preparation for further details.

Thinning is not required, though a small amount of water can be added if desired. Material that has been thinned is prone to in-can settling and biological contamination if not used immediately.

For best results, material, substrate and air temperature should be between 50 – 90°F (10 – 32°C) during application.

Product Data:

Sheen: <3.0 at 85° (Flat)

Volume Solids: 33%

Viscosity: 100-105 KU

VOC content: 30 g/L (0.25 lb/gal)

Weight Solids: 52%

Density: 11.7 lb/gal (1.4 g/mL)

Coverage: 350 ft² per gallon will yield a dried film thickness of 1.5 mils (theoretical coverage over non-porous substrates; actual results will depend upon porosity of the substrate).

Dry Time: Product dries to touch in 1 hour or less; may be recoated after four hours. Dry time may be affected by poor ventilation, low temperature, and/or high humidity areas.

Cleanup: Clean all tools and equipment with warm soapy water.

Environmental/Health Considerations: Formulated without lead, mercury, and other heavy metals. Does not contain ethylene glycol or crystalline silica.

Colorado Pro 600

Interior Latex Paint

0650 Series Flat

General Surface Preparation:

All foreign material, including loose or peeling paint, dirt, grease, oil, wax, chalk, mildew, rust, dust, curing agents, etc., must be removed prior to use. Failing to do so may compromise proper adhesion and overall performance. Caulk all cracks and open seams. Putty all nail holes. An appropriate primer should be used when coating bare or porous substrates. A stain blocking primer is recommended over areas where stains would 'bleed through' to the surface. Glossy surfaces should be dulled prior to coating, and rough or patched surfaces should be sanded.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC AND MAY CAUSE SERIOUS ILLNESS IF YOU ARE EXPOSED, ESPECIALLY FOR CHILDREN OR THOSE WHO ARE PREGNANT. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to minimize lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. For further information, contact the U.S.E.P.A. National Lead Information Hotline at 1-800-424-LEAD or visit www.epa.gov/lead.

Concrete/Masonry Block: New concrete should cure for at least 30 days prior to priming and painting. The surface pH should be below 10 before applying an alkali resistant primer. Block filler should be used over masonry block.

Metal: Ferrous metal should be primed with a waterborne or solventborne rust resistant metal primer. Non-ferrous metal and zinc treated metal should be primed with an all-purpose metal primer.

Drywall/Gypsum Board: Nails and screws should be countersunk and properly covered using putty or drywall mud, then sanded to be flush with the rest of the surface. Primer is recommended for new drywall and porous surfaces.

Wood: Unpainted wood should be sanded smooth, wiped, and primed with an appropriate primer. For redwood or cedar, a stain blocking primer should be used to prevent bleed-through from soluble stains.

Primers:

Concrete: 1251 Elevation 100% Acrylic Primer (Formerly 1261)

Drywall: 0610 Colorado Pro 600 Drywall Primer or 0710 Colorado Pro 700 Primer/Sealer

Metal: 1255 Elevation 100% Acrylic All-Prime or 1320 Rock-Hard DTM Primer

Plaster: 1251 Elevation 100% Acrylic Primer or 1255 Elevation 100% Acrylic All-Prime

Wood (non-tannin): 1251 Elevation 100% Acrylic Primer

Water Soluble Stains and tannin woods: 1255 Elevation 100% Acrylic All-Prime

Cement Block: 1250 Elevation 100% Acrylic Block Filler

Packaging:

Available in 1-gallon and 5-gallon containers. Special packaging available upon request.

Intended Use: To be used in a manner consistent with latex wall paints and finishes. Do not take internally. Keep out of reach of children. For interior use only. Not recommended for floors or high humidity areas. Keep from freezing.

The information provided in this product data sheet is given in good faith and applies only to the product's intended use. Specifications are subject to change without notice. January 2014